

## Oak Transparent Select

INSTITU1

CERTIFIED PRODUCT ID 0218 - 33879 - 001

Article number 10143425 (EIP2256D) Oak Wood Grading Select Product type 2-layer parquet Format 10mm Strip Prestige 10 x 70 x 470 mm Dimensions Top layer thickness 3,5 mm Core material / Spruce Connection T/G very suitable Floor heating Treatment Live Matt lacquer Appearance Golden floors Colour Transparent

## Bevel Number of slotted top layers Surface structure m<sup>2</sup> per carton Boards per carton Weight per carton (kg) m² per pallet Boxes per pallet Weight per pallet (kg) **EN Norm** FSC claim Performance classification Density

2

without bevel

| unbrushed          |
|--------------------|
| 2,63               |
| 30                 |
| 5                  |
| 94,68              |
| 36                 |
| 540                |
| EN 13489           |
| controlled sources |
| Class 1            |
| >= 500kg/m³        |







Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

CERTIFIED BY



## Product details / Technical properties

| Moisture content                         | 5-9%          |
|--|---------------|
| Fire protection classification           | Cfl-s1        |
| Content of formaldehyde                  | E 1           |
| PCP content                              | NPD           |
| Brinell Value (N/mm²)                    | 38            |
| Shrinking and swelling                   |               |
| Breaking strength                        | NPD           |
| Thermal conductivity (W/(m*K)            | 0,13          |
| Thermal resistance (m <sup>2*</sup> K)/W | 0,08          |
| Antislip performance (CE)                | USRV 33       |
| Antislip performance (DIN)               | R9            |
| Nobb.number                              | 57724622      |
| EAN Code                                 | 7035580216070 |