

Oak Transparent Select

Article number	10143429 (EIP22K6D)
Wood	Oak
Grading	Select
Product type	2-layer parquet
Format	10mm Strip Prestige
Dimensions	10 x 70 x 470 mm
Top layer thickness	3,5 mm
Core material	/ Spruce
Connection	T/G
Floor heating	very suitable
Treatment	Live Natural oil
Appearance	Golden floors
Colour	Transparent

Bevel Number of slotted top layers Surface structure m² per carton Boards per carton Weight per carton (kg) m² per pallet Boxes per pallet Weight per pallet (kg) EN Norm FSC claim **Biological durability** Density

Proc	duct details / Technica	l properties
without bevel	Moisture content	5-9%
2	Fire protection classification	Cfl-s1
unbrushed	Content of formaldehyde	E 1
2,63	PCP content	NPD
80	Brinell Value (N/mm²)	38
15	Shrinking and swelling	
94,68	Breaking strength	NPD
36	Thermal conductivity (W/(m*K)	0,13
540	Thermal resistance (m ^{2*} K)/W	0,08
EN 13489	Antislip performance (CE)	USRV 59
controlled sources	Antislip performance (DIN)	R10
Class 1	Nobb.number	53111058
>= 500kg/m³	EAN Code	7035580216117



Moisture content	5-9%
Fire protection classification	Cfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,13
Thermal resistance (m ^{2*} K)/W	0,08
Antislip performance (CE)	USRV 59
Antislip performance (DIN)	R10
Nobb.number	53111058
EAN Code	7035580216117

REAL







Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

