

Oak Transparent smoked Nature

10143435 (ELP23K6D) Article number Oak Wood Grading Nature Product type 2-layer parquet Format 10mm Strip Prestige 10 x 70 x 470 mm Dimensions Top layer thickness 3,5 mm Core material / Spruce Connection T/G very suitable Floor heating Live Natural oil Treatment Appearance Dark floors Colour Transparent

Bevel Number of slotted top layers

| Number of sioned top lay |
|--------------------------|
| Surface structure |
| m² per carton |
| Boards per carton |
| Weight per carton (kg) |
| m² per pallet |
| Boxes per pallet |
| Weight per pallet (kg) |
| EN Norm |
| FSC claim |
| Biological durability |
| Density |

| without bevel |
|--------------------|
| 2 |
| unbrushed |
| 2,63 |
| 80 |
| 15 |
| 94,68 |
| 36 |
| 540 |
| EN 13489 |
| controlled sources |
| Class 1 |
| >= 500kg/m³ |







| CE | | | |
|---------|--|--|--|
| | 06 | | |
| Boen AS | | | |
| | Topdalsveien 406–408, 4658 Tveit, Norway | | |
| | Parquet flooring according to EN 13489: 2017-12 and EN 14342-2013 9.5-23 mm total thickness; parquet for indoor use | | |
| | DOP 4658; NB 0766 | | |
| | Drl-sl; EL density $\simeq 500 \text{kg/m}^3$ thermal conductivity $\simeq 0.14 \text{ W/mK}$ | | |

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.



Product details / Technical properties

| Moisture content | 5-9% |
|--|---------------|
| Fire protection classification | Cfl-s1 |
| Content of formaldehyde | E 1 |
| PCP content | NPD |
| Brinell Value (N/mm²) | 38 |
| Shrinking and swelling | |
| Breaking strength | NPD |
| Thermal conductivity (W/(m*K) | 0,133 |
| Thermal resistance (m ^{2*} K)/W | 0,075 |
| Antislip performance (CE) | USRV 59 |
| Antislip performance (DIN) | R10 |
| Nobb.number | |
| EAN Code | 7035580216315 |