

| Article number | 10152280 (EBG823ND) | Bevel | beveled 4V | Moisture content | 5-9% |
|---------------------|--------------------------------|--------------------------------|-----------------|--|------------------|
| Wood | Oak | Number of slotted top layers | 0 | Fire protection classification | Dfl-s1 |
| Grading | Adagio | Surface structure | Brushed | Content of formaldehyde | E1 |
| Product type | 3-Layer | m² per carton | 0,95 | PCP content | NPD |
| Format | Herringbone Click, B- Plank | Boards per carton | 10 | Brinell Value (N/mm²) | 38 |
| Dimensions | 9/16 x 5-7/16 x 27-3/16 inch | Weight per carton (kg) | 11 | Shrinking and swelling | |
| Top layer thickness | 3,5 mm | m² per pallet | 46,55 | Breaking strength | NPD |
| Core material | HDF / Spruce | Boxes per pallet | 49 | Thermal conductivity (W/(m*K) | 0,143 |
| | | | | | |
| Connection | 5G Click | Weight per pallet (kg) | 539 | Thermal resistance (m ^{2*} K)/W | 0,098 |
| Floor heating | 5G Click suitable | Weight per pallet (kg) EN Norm | 539 EN 13489 | Thermal resistance (m ^{2*} K)/W Antislip performance (CE) | 0,098 USRV 91 |
| | | | | , , | |
| Floor heating | suitable | EN Norm | EN 13489 | Antislip performance (CE) | USRV 91 |

















Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

