# Oak Medium Grey

Product details / Technical properties

| | | | | | |
|---|---|---|---|---|---|
| **Article number** | 10152606 | **Bevel** | beveled 2V | **Moisture content** | 5-9% |
| **Wood** | Oak | **Number of slotted top layers** | 2 | **Fire classification (floating)** | Dfl-s1 |
| **Grading** | Animoso Mix | **Surface structure** | deep brushed | **Fire classification (glued)** | Cfl-s1 |
| **Product type** | 3-layer parquet | **m² per carton** | 3.04 | **Content of formaldehyde** | E 1 |
| **Format** | Plank 138 | **Boards per carton** | 10 | **PCP content** | NPD |
| **Dimensions** | 14 x 138 x 2200 mm | **Weight per carton (kg)** | 25.5 | **Brinell Value (N/mm²)** | 38 |
| **Top layer thickness** | 3.5 mm | **m² per pallet** | 127.68 | **Breaking strength** | NPD |
| **Core material** | Spruce / Spruce | **Boxes per pallet** | 42 | **Thermal conductivity (W/(m*K)** | 0.129 |
| **Connection** | 5G® Click | **Weight per pallet (kg)** | 1071.0 | **Thermal resistance (m²*K)/W** | 0.109 |
| **Floor heating** | suitable | **EN Norm** | EN 13489 | **Antislip performance (CE)** | USRV 57 |
| **Treatment** | Live Matt Plus | **FSC claim** | controlled sources | **Antislip performance (DIN)** | |
| **Appearance** | medium | **Performance classification** | Class 1 | **Nobb.number** | 60039904 |
| **Colour** | Medium Grey | **Density** | >= 500kg/m³ | **EAN Code** | 7035580219514 |

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.