Oak Medium Grey

Product details / Technical properties

Article number	10157339	**Bevel**	beveled 2V	**Moisture content**	5-9%
Wood	Oak	**Number of slotted top layers**	1	**Fire classification (floating)**	Dfl-s1
Grading	Animoso Mix	**Surface structure**	deep brushed	**Fire classification (glued)**	Cfl-s1
Product type	3-layer parquet	**m² per carton**	3.19	**Content of formaldehyde**	E 1
Format	Plank 181	**Boards per carton**	8	**PCP content**	NPD
Dimensions	13.2 x 181 x 2200 mm	**Weight per carton (kg)**	23	**Brinell Value (N/mm²)**	38
Top layer thickness	2.7 mm	**m² per pallet**	127.6	**Breaking strength**	NPD
Core material	Spruce / Spruce	**Boxes per pallet**	40	**Thermal conductivity (W/(m*K)**	0.13
Connection	5G® Click	**Weight per pallet (kg)**	920.0	**Thermal resistance (m²*K)/W**	0.1
Floor heating	suitable	**EN Norm**	EN 13489	**Antislip performance (CE)**	USRV 57
Treatment	Live Matt Plus	**FSC claim**	controlled sources	**Antislip performance (DIN)**	
Appearance	medium	**Performance classification**	Class 1	**Nobb.number**	60114726
Colour	Medium Grey	**Density**	>= 500kg/m³	**EAN Code**	7035580225843

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.